



## Introduction to Computational Logic, SS 2006: Hints for Assignment 6

Prof. Dr. Gert Smolka, Dipl.-Inform. Mathias Möhl

### Exercise 6.5 a)

$$\begin{aligned}xx &= xx + 0 && \text{Id} \\ &= xx + x\bar{x} && \text{Compl} \\ &= x(x + \bar{x}) && \text{Distr} \\ &= x1 && \text{Compl} \\ &= x && \text{Id}\end{aligned}$$

### Exercise 6.8 a) UoC yields for $\{b := x, a := \bar{x}\}$

$$\{\bar{x}x = 0, \bar{x} + x = 1\} \stackrel{\text{BA}}{\vdash} \{x = \bar{\bar{x}}\}$$

Since the equations on the left are deducible from BA, we have

$$\emptyset \stackrel{\text{BA}}{\vdash} \{x = \bar{\bar{x}}\}$$

and therefore  $\text{BA} \vdash x = \bar{\bar{x}}$

### Exercise 6.9

a)  $\stackrel{\text{BL}}{\vdash}$ :

$$\begin{aligned}ab &= 1b && a = 1 \\ &= 11 && b = 1 \\ &= 1 && \text{Id}\end{aligned}$$

$\stackrel{\text{BL}}{\vdash}$ :

$$\begin{aligned}a &= a(a + b) && \text{Abs} \\ &= aa + ab && \text{Distr} \\ &= aa + 1 && ab = 1 \\ &= 1 && \text{Dom}\end{aligned}$$

$b$  analogously